

## HT-W WiFi Antenna

**600-2700 (MHz) 5dB black glue rod antenna +SMA male**

**head female needle**



---

## 1. Product Overview:





## 2. Specifications:

Main technical specifications			
Frequency range (MHZ)	600-2700mhz	Frequency Range (MHZ)	600-2700mhz
The characteristic impedance( $\Omega$ )	50	Impedance( $\Omega$ )	50
Gain(dBi)	5	Gain(dBi)	5
Bandwidth (MHz)	48	Bandwidth (MHz)	48
The output voltage Standing wave ratio	$\leq 1.5$	VSWR	$\leq 1.5$
Polarization mode	Vertical	Polarization	Vertical
Max Input Power (w)	50	Max Input Power (w)	50
Physical Properties			
Size(cm)		Antenna size(cm)	
The Connection method	SMA	Connector Type	SMA
Temperature	-20°C~+40°C	Storage Temp	-20°C~+40°C
Temperature	-40°C~+60°C	Working Temp	-40°C~+60°C
Radiator	Cuprum	Radiator	Cuprum
Radome Color	Black	Radome Color	Black
Material	Plastic	Material	Plastic

---

### 3. Test report:



---

#### 4. Common issues:

- The antenna frequency must match the frequency of the wireless device, otherwise the communication effect is not good;
- The lower the communication frequency, the longer the wavelength, the better the diffraction performance.
- When there is a linear communication obstacle, the communication distance will be attenuated accordingly.
- Note the antenna radiation direction. Incorrect antenna installation direction may result in a short transmission distance.
- Sea water has a strong ability to absorb radio waves, so the seaside test results are not good;

