




HT-HC33

ESP-HaLowCamera

ESP32-S3 Dev-board

with Camera and WiFi HaLow



Document version

Version	Time	Description	Remark
Rev. 1.0	2024-10-16	P-Development version	Richard

Copyright Notice

All contents in the files are protected by copyright law, and all copyrights are reserved by Chengdu Heltec Automation Technology Co., Ltd. (hereinafter referred to as Heltec). Without written permission, all commercial use of the files from Heltec are forbidden, such as copy, distribute, reproduce the files, etc., but non-commercial purpose, downloaded or printed by individual are welcome.

Disclaimer

Chengdu Heltec Automation Technology Co., Ltd. reserves the right to change, modify or improve the document and product described herein. Its contents are subject to change without notice.

These instructions are intended for you use.

Content

HT-HC32	1
Document version	2
Copyright Notice	2
Disclaimer	2
Content	3
1 Description	4
1.1 Overview	4
1.2 Product Features	5
1.3 Application	6
2 Pin description	7
3 Specifications	10
3.1 Generic Parameter	10
3.2 Wi-Fi HaLow Parameters	11
3.3 Camera Parameters	11
4 Electrical Characteristics	12
4.1 Battery voltage detection circuit	12
4.2 Operating Voltage	13
4.3 Power consumption	13
5 RF Characteristics	14
5.1 Receiver sensitivities	14
5.2 Transmitter Power	14
6 Get Started(SDK)	15
7 Hardware Dimensions	15
7.1 Board dimensions (unit: mm)	15
7.2 Camera dimensions (unit: mm)	16
8 Resource	17
8.1 Relevant resource	17
8.2 Heltec Contact Information	17

1 Description

1.1 Overview

HT-HC33 is a development board with integrated **camera**, based on the **ESP32-S3 MCU** and **Wi-Fi HaLow** module. It is designed for **long-range, high-speed** wireless communication. With support for transmission distances of over 1 km and speeds of up to 32 Mbps, it is ideal for IoT applications that require reliable, high-performance connectivity.

The module features a **low power consumption design** with **excellent signal penetration**, ensuring robust performance even in challenging environments. The integrated camera has a 200-pixel wide-angle, which supports **advanced image processing functions** such as auto exposure control, auto gain control, image scaling, and image compression.

For easy local data storage and deployment, the device includes an integrated **SD card slot**. Additionally, the **USB-C** interface provides **built-in protection**, including voltage regulation, ESD protection, short circuit protection, and RF shielding, ensuring durability and safety.

HT-HC33's connectivity options include Wi-Fi, Bluetooth, and Wi-Fi HaLow, with an onboard 2.4 GHz patch antenna for Wi-Fi and Bluetooth, as well as a reserved IPEX (U.FL) interface for the HT-HC01 Wi-Fi HaLow module. The integration of the **CP2102** USB-to-serial chip enables easy program downloading and debugging, while the system is fully compatible with the **Arduino development environment**, offering a flexible platform for rapid prototyping and development.

1.2 Product Features

- The MCU is the ESP32-S3, and the Wi-Fi HaLow module is HT-HC01.
- Long transmission range, up to over 1~2km.
- Fast transmission speed, with a maximum of 32 Mbps.
- Low power consumption design with strong penetration.
- Integrated 300M-pixel wide-angle camera
- Integrated SD card slot for easy local deployment and data storage.
- USB-C interface with a complete voltage regulator, ESD protection, short circuit protection, RF shielding, and other protection measures.
- Onboard SH1.25-2 battery interface, integrated lithium battery management system (charging and discharging management, overcharge protection, battery power detection, USB/battery power automatic switching).
- Integrated Wi-Fi, Bluetooth, and Wi-Fi HaLow three network connections, with onboard 2.4 GHz patch antenna for Wi-Fi and Bluetooth, and reserved IPEX (U.FL) interface for Wi-Fi HaLow.
- Integrated CP2102 USB-to-serial chip, convenient for program downloading and debugging information printing.
- Compatible with Arduino.

1.3 Application

The HT-HC33 features a powerful MCU and extensive resources, allowing it to be used both as a standard ESP32 or Wi-Fi HaLow development board, and as a specialized platform when paired with a camera for specific applications.


- ◆ Remote camera monitoring
- ◆ Industrial automation control
- ◆ Asset management and tracking
- ◆ Smart home
- ◆ Smart city
- ◆ Smart farming
- ◆ Construction Site Management
- ◆ Wi-Fi/Ethernet/Wi-Fi_HaLow extension and bridging
- ◆ Proximity sensors
- ◆ Rural internet access
- ◆ Autonomous driving
- ◆ Mobile phone location
- ◆ Environmental monitoring
- ◆ Unmanned supermarket
- ◆ Commodity management
- ◆ Intelligent lighting controls

2 Pin description

I²C and SPI

Each IO pin is preconfigured with **IO_MUX** functionality, which means you can use any GPIO as I²C or SPI pins. You just need to define these pins in your code. However, it's important to note that once a pin is used, it may affect other functions associated with that pin.

- For information not available in the "Pin Description," please refer to the [HT-HC33 Schematic](#).



J1

NO.	Name	Type	Description
1	5V	Power	5V Power
2	GND	Power	Ground
3	RST	I	Reset
4	21	I/O	GPIO21, PCLK
5	20	I/O	GPIO20, ADC_Ctrl, USB_P, U1CTS, ADC2_CH9
6	19	I/O	GPIO19, LED, USB_N, U1RTS, ADC2_CH8
7	18	I/O	GPIO18, Y6, U1RXD, ADC2_CH7
8	17	I/O	GPIO17, Y2, U1TXD, ADC2_CH6
9	16	I/O	GPIO16, SD_MISO, U0CTS, ADC2_CH5
10	15	I/O	GPIO15, SD_CLK, U0RTS, ADC2_CH4
11	14	I/O	GPIO14, Y5, FSPIIOQS, FSPIWP, SUBSPIWP, ADC2_CH3
12	13	I/O	GPIO13, Y3, FSPIIO7, FSPIQ, SUBSPIQ, ADC2_CH2
13	12	I/O	GPIO12, Y4, FSPIIO6, FSPICLK, SUBSPICLK, ADC2_CH1
14	11	I/O	GPIO11, SD_MOSI, FSPIIO5, FSPID, SUBSPID, ADC2_CH0
15	10	I/O	GPIO10, SD_CS, FSPIIO4, FSPICS0, SUBSPICS0, ADC1_CH9

J2

NO.	Name	TYPE	Description
1	3V3	Power	3V3 Power
2	GND	Power	Ground
3	0	I/O	GPIO0, USER key

4	1	I/O	GPIO1, ADC_IN
5	48	I/O	GPIO48, SPICLK_N, Y8, SPI CLK_N_DIFF,SUBSPI CLK_N_DIFF
6	47	I/O	GPIO47, SPICLK_P, XCLK, SPI CLK_P_DIFF,SUBSPI CLK_P_DIFF
7	38	I/O	GPIO38, Y9, FSPIWP, SUBSPIWP
8	39	I/O	GPIO39,MTCK, HREF
9	40	I/O	GPIO40,MTDO, VSYNC
10	41	I/O	GPIO41,MTDI, ResetB
11	42	I/O	GPIO42,MTMS, SIO_C
12	TX	I/O	GPIO43,U0TXD
13	RX	I/O	GPIO44,U0RXD
14	45	I/O	GPIO45, SIO_D
15	46	I/O	GPIO46, Y7

3 Specifications

3.1 General Parameter

Table 3.1 General parameter

Parameters	Description
MCU	ESP32-S3R8
Wi-Fi HaLow Module	HT-HC01(MM6108Q)
Serial port chip	CP2102
Wi-Fi HaLow	IEEE 802.11ah
Memory	384KB ROM; 512KB SR; 16KB RTC SRAM; 8M PSRAM, 16MB SiP Flash
Interface	HaLow ANT connector(IPEX1.0); 2.4G ANT connector(IPEX1.0) ^① , 2*15*1.27 Header Pins, 24P_0.5mm FFC connector(camera), USB-C, SH1.25-2P battery interface, Micro-SD card holder
Power Supply	5V@USB, 3.4~4.2V@Battery
Power consumption	See Table
Sleep consumption	See Table
Operating temperature	-40 ~ +85°C
Operating humidity	10% ~ 90%, no-condensing
Dimensions	60.00*33.50*7.10mm ³ (excluding Micro-SD and camera)

^① Default connection uses the onboard antenna. For IPEx antenna connection, please refer to:

https://docs.heltec.org/en/wifi_halow/ht-hc33/faq.html

3.2 Wi-Fi HaLow Parameters

Table 3.2 Wi-Fi HaLow Parameters


Parameter	Description
Module	HT-HC01(MM6108Q)
Wi-Fi Standard	IEEE 802.11ah
Frequency	902-928 MHz
Max Data Rate	32.5 Mbps
Band Width	1/2/4/8MHz
Receiver sensitivities	Table
Transmitter Power	Table

3.3 Camera Parameters

Refer to: <https://resource.heltec.cn/download/HT-HC33/CAMERA>

4 Electrical Characteristics

4.1 Battery voltage detection circuit



4.2 Operating Voltage

Stress beyond absolute maximum ratings may cause permanent damage to the module. Functional operation is guaranteed for recommended operation conditions only. Operation of the device outside the recommended conditions may result in a reduced lifetime and/or reliability problems (even if the absolute maximum ratings are not exceeded).

Table3.3.1 Operating Voltage

Parameter	Min	Typical (recommended)	Max	Units
Voltage @USB		5		V
Voltage @Battery		3.7		V

4.3 Power Consumption

Table3.3.1 power consumption

Parameter	Min	Typical	Max	Units
Wi-Fi	AP	175	195	mA
	SCAN	144		mA
	Client	80	92	160
Wi-Fi HaLow STA	120	160	192	mA
Camera_Web_Server ^②		220		mA

^② LAN monitoring via Wi-Fi HaLow.

5 RF Characteristics

5.1 Receiver sensitivities

Table 5.1 Receiver sensitivities

Minimum Receive sensitivity (dBm) per BW			
1 MHz	2 MHz	4 MHz	8 MHz
-105	-103	-101	-97
-102	-100	-97	-93
-99	-97	-95	-91
-96	-94	-91	-88
-93	-90	-88	-85
-89	-87	-84	-80
-88	-85	-83	-79
-87	-84	-81	-77
-107	N/A		

5.2 Transmitter Power

Table 5.2 Transmitter power

BW		Min(dBm)	Typical(dBm)	Max(dBm)
1/2MHz	MCS 0	20	21	22
	MCS 7	16	17	18.5
4MHz	MCS 0	20.5	21	22
	MCS 7	16	17	18
8MHz	MCS 0	20.5	21	21.5
	MCS 7	15.5	17	17.5

<https://heltec.org>


6 Software

Heltec provides an [Arduino](#)-based development framework:

- GitHub Link- [Heltec ESP32 HaLow Development Framework](#)
- [Installation and Getting Started Guide.](#)

7 Hardware Dimensions


7.1 Board dimensions (unit: mm)




7.2 Camera dimensions (unit: mm)

Camera resource: <https://resource.heltec.cn/download/HT-HC33/CAMERA>

OV3660-21MM-60°



OV3660-21MM-120°



8 Resource

8.1 Relevant resource

- Documents Page: [Heltec Products Operation Documentation](#)
- Schematic diagram: [listing directory /download/HT-HC32/Schematic_diagram](#)
- Resource station: [resource.heltec.cn](#)

8.2 Heltec Contact Information

Heltec Automation Technology Co., Ltd

Chengdu, Sichuan, China

Email: support@heltec.cn

Phone: +86-028-62374838

<https://heltec.org>